

Trimble R750 Model 2

MODULAR GNSS RECEIVER

Base station solution with advanced technologies for accurate and reliable data.



Connected receiver for precision and flexibility

Advanced

Trimble® ProPoint® GNSS positioning engine. Engineered for improved accuracy and productivity in challenging GNSS conditions.

Trimble Maxwell™ 7 GNSS ASIC dual chipset tracks the latest signals from all GNSS constellations with improved EVEREST™ Plus multipath mitigation, interference detection, and protection against GNSS spoofing.

Trimble IonoGuard™ technology mitigates ionospheric GNSS signal disruptions.

Data logging internally and to external drive.

USB-C PD charging.

Convenient 4-line front panel display and configuration.

Connected

Integrated 450/900 MHz dual-band UHF radio.

Integrated worldwide 4G LTE modem.

Bluetooth® and Wi-Fi® data connectivity.

Ethernet, serial and USB support.

Trimble CenterPoint® RTX correction service delivers global RTK-level precision without a base station or real-time network.

Trimble xFill® correction outage technology.

Stream RTK corrections over the internet with the Trimble Internet Base Station Service (IBSS).

Flexible

Choice of configuration and features to meet the needs of your job.

Flexibility to add more functionality as requirements change.



Find out more at:
geospatial.trimble.com/r750
civilconstruction.trimble.com/r750

Trimble R750 Model 2

Modular GNSS receiver



CONFIGURATION OPTION

MODULAR

| | |
|---|---|
| Base and Rover interchangeability | Yes, upgradeable to Rover, Base or Rover and Base |
| Rover position update rate | 1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 Hz, 50 Hz |
| Rover maximum range from base | Unrestricted, typical range 2–5 km (1.2–3 miles) without radio repeater |
| Rover operation within a Trimble VRS™ network | Yes |
| Heading and Moving Base operation | Yes |
| Internal Memory | 9.25 GB logging |

GENERAL

KEYBOARD AND DISPLAY

| | |
|------------------------|--|
| | OLED Display (256 x 64), 32 characters by 4 rows |
| | On/Off key for one-button startup |
| | Escape and Enter keys for menu navigation |
| | 4 arrow keys (up, down, left, right) for option scrolls and data entry |
| Dimensions (L x W x D) | 269 mm (10.6 in) x 141 mm (5.5 in) x 61 mm (2.4 in) |
| Weight | 2.05 kg (4.52 lb) |

GNSS ANTENNA (Recommended)

| | |
|--|---|
| Zephyr™ 3 or Zephyr Model 2 series [Base, Rover, Rugged, Geodetic] | Triple-frequency GNSS (GPS, GLONASS, Galileo, BeiDou, QZSS, NavIC) MSS, SBAS |
| GA830 | Triple-frequency GNSS (GLONASS, Galileo, BeiDou, QZSS), MSS, SBAS |
| LNA Filters | Japanese LTE filtering below 1510 MHz allows usage >100 m from LTE cell tower Iridium filtering above 1616 MHz allows usage >20 m from Iridium transmitter |

TEMPERATURE

| | |
|--------------------------|--|
| Operating ¹ | -40 °C to +65 °C (-40 °F to +149 °F) |
| Storage | -40 °C to +80 °C (-40 °F to +176 °F) |
| Humidity | 93% humidity at 40 °C for a duration of 3 hours (IEC-60945 Method 8.3) |
| Water ingress protection | IP67 for temporary submersion to depth of 1 m (3.3 ft), dust-proof |

SHOCK AND VIBRATION

| | |
|-----------------------|--|
| Pole drop | Designed to survive a 1.1 m (3.6 ft) pole drop onto a hard surface |
| Shock – Non-operating | To 75 g, 6 ms |
| Shock – Operating | To 40 g, 10 ms, saw-tooth |
| Vibration | IEC 60945 Method 8.7 Random 6.2 g RMS operating 9.8g RMS 24–2000 Hz for 1 hrs each axis survival |

GNSS TECHNOLOGY

| |
|---|
| Advanced Trimble Maxwell 7 custom GNSS dual chipset |
| Constellation agnostic, flexible signal tracking with Trimble ProPoint technology |
| Unfiltered, unsmoothed pseudo-range measurements data for low noise, low multipath error, low-time domain correlation, and high-dynamic response |
| Trimble EVEREST multipath signal rejection |
| Trimble IonoGuard technology for mitigation of ionospheric GNSS signal disruptions |
| Spectrum Analyser to troubleshoot GNSS jamming |
| Anti-spoofing capabilities |
| Trimble xFill technology for short gaps in correction messages |
| Multi-channel GNSS [672 channels] |
| GPS: L1 C/A, L1C, L2C, L5, L2E (Trimble method for tracking unencrypted L2P) |
| GLONASS: L1-C/A, L2-C/A, L2P, L3 |
| Galileo: E1, E5A, E5B & E5AltBOC ² , E6. |
| BeiDou: B1, B1C, B2, B2A, B2B, B3 |
| SBAS L1 C/A (EGNOS/MSAS/GAGAN,SDCM), L1 C/A, L5 (WAAS) |
| QZSS: L1 C/A, L1C, L1S, L2C, L5, L6D, L6E |
| NavIC (IRNSS) L5-C/A |
| MSS Band (2-channels): Trimble CenterPoint RTX correction service and Omnistar®/Marinestar® by subscription |
| Trimble CenterPoint RTX corrections service is ready to use for 12 months from TIM Activation. Learn more at tx.trimble.com |

Trimble R750 Model 2

Modular GNSS receiver

| POSITIONING | |
|---|--|
| REGIONAL SBAS POSITIONING³ | |
| WAAS, MSAS, EGNOS, QZSS, GAGAN, SDCM, SouthPAN | |
| Accuracy | Horizontal ± 0.50 m (1.6 ft), Vertical ± 0.85 m (2.8 ft) |
| PRECISE POINT POSITIONING (PPP) | |
| Galileo HAS, SL1 [global] ² | Horizontal ± 0.20 m (0.7 ft), Vertical ± 0.40 m (1.3 ft), Convergence 300 s |
| QZSS CLAS [Japan only] ² | Horizontal 0.07 m (0.2 ft) RMS, Vertical ± 0.12 m (0.4 ft) RMS |
| CODE DIFFERENTIAL GPS POSITIONING⁴ | |
| Horizontal accuracy | $\pm(0.25 \text{ m} + 1 \text{ ppm})$ RMS $\pm(0.8 \text{ ft} + 1 \text{ ppm})$ $\pm(250+1 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| Vertical accuracy | $\pm(0.50 \text{ m} + 1 \text{ ppm})$ RMS $\pm(1.6 \text{ ft} + 1 \text{ ppm})$ $\pm(500+1 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| OMNISTAR POSITIONING | |
| VBS service accuracy | Horizontal <1 m (3.3 ft) |
| XP service accuracy | Horizontal 0.2 m (0.66 ft), Vertical 0.3 m (1.0 ft) |
| HP service accuracy | Horizontal 0.1 m (0.33 ft), Vertical 0.15 m (0.5 ft) |
| Marinestar G2+ service accuracy | Horizontal 0.02 m (0.06 ft), Vertical 0.06 m (0.20 ft), 95% |
| CENTERPOINT RTX POSITIONING⁵ | |
| Convergence time for specified precisions | <1 min [RTX Fast regions], <3 min [Worldwide] |
| CenterPoint RTX accuracy (with valid subscription) | Horizontal 0.02 m (0.06 ft) RMS, Vertical 0.03 m (0.1 ft) RMS |
| xFill mode (limited to 5 minutes) ^{6,7} | RTK Horizontal + 10 mm (0.03 ft)/min RMS, RTK Vertical + 20 mm (0.06 ft)/min RMS |
| xFill-RTX mode (with valid CenterPoint RTX subscription) ^{6,7} | Horizontal 0.03 m (0.01 ft) RMS, Vertical 0.07 m (0.2 ft) RMS |
| REAL-TIME KINEMATIC POSITIONING⁴ | |
| Horizontal accuracy | 8 mm + 1 ppm RMS (0.026 ft + 1 ppm RMS) $\pm(8+1 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| Vertical accuracy | 15 mm + 1 ppm RMS (0.05 ft + 1 ppm RMS) $\pm(15+1 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| NETWORKED RTK⁸ | |
| Horizontal accuracy | 8 mm + 0.5 ppm RMS $\pm(8+0.5 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| Vertical accuracy | 15 mm + 0.5 ppm RMS $\pm(15+0.5 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| PRECISE HEADING | |
| Heading accuracy | With incoming Moving Base CMRx corrections |
| 2 m antenna separation | 0.09° RMS |
| 10 m antenna separation | 0.05° RMS |
| HIGH PRECISION STATIC | |
| Horizontal accuracy | 3 mm + 0.1 ppm RMS (0.01 ft + 0.1 ppm) $\pm(3+0.1 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| Vertical accuracy | 3.5 mm + 0.4 ppm RMS (0.011 ft + 0.4 ppm) $\pm(3.5+0.4 \times D \times 10^{-6})$ mm [D = distance from base in Km] |
| VELOCITY | |
| Doppler horizontal accuracy | H 0.008 m/s RMS, V 0.025 m/s RMS |
| INITIALISATION TIME | |
| Regular RTK operation with base station | Single/Multi-base |
| Initialisation | 2–8 seconds |
| Initialisation reliability ⁹ | >99.9% |

| POWER AND COMMUNICATIONS | |
|---|--|
| Internal | Integrated internal battery 7.26 V, 6700 mAh, Lithium-ion |
| | Internal battery operates as a UPS during an ext power source failure |
| | Internal battery will charge from USB-PD source or approved AC power supply |
| External | Integrated charging circuitry |
| | Power input on 7-pin 0-shell Lemo connector is optimised for lead acid batteries with a cut-off threshold of 11.5 V. Max 28 V DC |
| | Power input on the 26-pin D-sub connector has a cut-off threshold of 10.5 V |
| | Power supply will hot-swap between internal and external sources |
| | USB-PD input from device capable of 15V @ 2A |
| Power consumption | DC external power input with over-voltage protection |
| | Receiver automatically turns on when connected to external power |
| | 6.6 W in rover mode with internal receive radio 8.5 W in base mode with internal transmit radio |
| OPERATION TIME ON INTERNAL BATTERY | |
| Rover | 7 hrs: CMRx over UHF 7 hrs: VRS/IBSS over LTE (Internal or Controller via BT) |
| Base station | 450 MHz: 5.5 hrs (0.5 W), 5.0 hrs (1 W): CMRx over UHF and LTE |
| | 900 MHz: 7 hrs: CMRx over UHF and LTE |
| Adding a USB-PD Powerpack (30,000 mAh) to a fully charged internal battery will provide ~13.9 hrs @ 11.4 W for a 450 MHz at 1 W | |
| REGULATORY APPROVALS | |
| Country Compliance Notices | |
| COMMUNICATIONS | |
| Serial 1 (COM1) | 7-pin 0S Lemo, Serial 1, 3-wire RS-232 |
| Serial 2 (COM2) | 26-pin D-sub, Serial 2, 5-wire RS232, using adaptor cable (Selectable) |
| | 26-pin D-sub, Serial 2, 4-wire RS422, using adaptor cable (Selectable) |
| Serial 3 (COM3)/CAN | 26-pin D-sub, Serial 3, 3-wire RS232, using adaptor cable (Selectable) |
| | 2 wire CAN Output [NMEA 2000] (Selectable) |
| Serial 4 (COM4) | 26-pin D-sub, Serial 4, 4-wire RS422, using adaptor cable (Selectable) |
| 1PPS (1 Pulse-per-second) | Supported on both Lemo and 26-pin D-sub |
| Event In | Supported on Lemo |
| USB | USB v2 (Supports USB-PD charging) |
| Ethernet | Through a multi-port adaptor (PN 57168) |
| Wi-Fi | Fully-integrated, fully-sealed 2.4 GHz Wi-Fi module |
| Bluetooth wireless technology | Simultaneous Access Point (AP) and Client modes |
| | Fully-integrated, fully-sealed 2.4 GHz Bluetooth module ¹⁰ |
| Cellular | Fully-integrated, fully-sealed LTE compliant module |
| | Nano-SIM card |
| | FDD-LTE: bands 1, 2, 3, 4, 5, 7, 8, 12, 13, 18, 19, 20, 26, 28, 66 |
| | TD-LTE: bands 38, 40, 41 UMTS (WCDMA/FDD): bands 1, 3, 2, 4, 5, 6, 8, 19 Quad Band GSM: 850, 900, 1800, 1900 MHz |

Trimble R750 Model 2

Modular GNSS receiver

| NETWORK PROTOCOLS | |
|---|---|
| HTTP (web browser GUI) | HTTP, HTTPS |
| NTP Server | Yes |
| TCP/IP or UDP | Yes |
| NTRIP | NTRIP v1 and v2, Client, Server and Caster modes |
| mDNS/uPnP Service discovery | Yes |
| Dynamic DNS | Yes |
| eMail alerts | Supports SSL/TLS secure Email Servers |
| INTEGRATED RADIO (Hardware dependant) | |
| Fully-integrated, fully-sealed internal 403-473 MHz or dual band 410-475 MHz / 902-928 MHz; Rx/Tx | |
| 450 MHz Band | 12.5 kHz or 25 kHz spacing available |
| Sensitivity | -114 dBm (12 dB SINAD) |
| Transmit power | 0.1 W, 0.5 W, 1.0 W [Configured by Trimble Dealer] |
| Frequency approvals | 403-473 MHz (PN 218500-40) ETSI Compliant 410-475 MHz (PN 218500-50) Worldwide excluding UAE/S. Africa/Thailand (Depending on the local licensing) |
| 900 MHz Band | Fully-integrated, internal 900 MHz; Tx/Rx [1.0 W] |
| Frequency approvals (902-928 MHz) | USA/Canada/Australia/NZ |
| INTERNAL MSS DEMODULATOR (L-BAND) | |
| Channels | 2 |
| Frequency range | 1525-1559 MHz |
| Correction Services ¹¹ | Trimble CenterPoint RTX, OmniSTAR and Fugro Marinestar |
| CELLULAR SUPPORT | |
| Internet-based correction streams: (IBSS, VRS, NTRIP) | Internal LTE modem Connected smartphone Connected Trimble Controller (SiteWorks, Trimble Access™) |
| Remote access | Using DynDNS and appropriate service |

- 1 Operating up to +65 °C ambient when the device is powered by external DC supply and the battery is fully charged or is not being charged. Operating up to +30 °C ambient when the battery is being charged by an external DC supply. Operating up to +48 °C ambient when the device is powered by a USB-PD battery or charger.
- 2 The receivers' current capability is based on publicly available information. As such, Trimble cannot guarantee they will be fully compatible with future generations of Galileo and QZSS satellites or signals.
- 3 Depends on SBAS system performance.
- 4 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, interference and atmospheric conditions. Always follow recommended survey practices.
- 5 Receiver accuracy and convergence time varies based on GNSS constellation health, level of multipath, and proximity to obstructions such as large trees and buildings.
- 6 Accuracies are dependent on GNSS satellite availability. xFill positioning without an xFill Premium subscription ends after 5 minutes of radio downtime. xFill Premium will continue beyond 5 minutes providing the solution has converged, with typical precisions not exceeding 3 cm horizontal, 7 cm vertical. xFill is not available in all regions, check with your local sales representative for more information.
- 7 RTK refers to the last reported precision before the correction source was lost and xFill started.
- 8 Networked RTK PPM values are referenced to the closest physical base station.
- 9 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialisation reliability is continuously monitored to ensure highest quality.
- 10 Bluetooth type approvals are country specific. For more information, contact your local Trimble office or representative.
- 11 Correction services supported are subject to regional availability.
- 12 Standard options are dependent on country compliance for Wi-Fi and LTE.
- 13 Available upgrades may differ by region.

Specifications subject to change without notice.

| INPUT/OUTPUT | |
|---|--|
| Correction data | CMR, CMR+™, CMRx, RTCM 2.x, RTCM 3, RTCM 3.3(MSM) MSS [Marinestar, Trimble RTX®] |
| Data outputs | NMEA 0183, NMEA 2000, GSOFF, 1PPS Time Tags, RT17, RT27 |
| Data inputs | Event |
| Maximum data rate | 50 Hz (depending on data type) |
| FEATURES AND UPGRADES | |
| Standard Options ¹² | RTX Rover, GPS, GLN, BDS, GAL, QZSS, SBAS, 3F, xFill, NMEA, Wi-Fi, Logging, Field Radio, Moving Base |
| Raw data logging (*.T02, *.T04) | 9.25 GB Internal |
| Precision upgrades ¹³ | Precise Base, Precise Rover with Base as backup, Rover 10/2, Rover 10/10 |
| Signal / Constellation upgrades | All constellations and signals are included as standard |
| Feature upgrades | Programmatic interface |
| TRIMBLE PROTECTED PROTECTION PLANS | |
| Add a Trimble Protected protection plan for worry-free ownership over and above the standard Trimble product warranty. Added enhancements include coverage for wear & tear, environmental damage, and more. Accidental damage is covered with Premium plans, available only at point-of-sale in selected regions. For details, visit trimbleprotected.com or contact a local Trimble distributor. | |



PT. GPS LANDS INDOSOLUTIONS

Jl. Ciputat Raya No. 4F, Kebayoran Lama
Jakarta 12240 - Indonesia
Telp : +62 21 7238381 Fax : +62 21 7238403
Email : Info@gpslands.co.id
Website : www.gpslands.co.id

NORTH AMERICA

Trimble Inc.
10368 Westmoor Dr
Westminster CO 80021
USA

EUROPE

Trimble Germany GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY

ASIA-PACIFIC

Trimble Navigation
Singapore PTE Limited
3 HarbourFront Place
#13-02 HarbourFront Tower Two
Singapore 099254
SINGAPORE

